

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets

(11) Publication number:

0 402 250
A2

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 90401539.3

(51) Int. Cl.⁵: A61B 17/36, A61F 9/00

(22) Date of filing: 06.06.90


(30) Priority: 07.06.89 US 363174

(43) Date of publication of application:
12.12.90 Bulletin 90/50(84) Designated Contracting States:
DE ES FR GB IT(71) Applicant: UNIVERSITY OF MIAMI
School of Medicine, Department of
Ophthalmology, 1638, N.W., 10th Ave.
Miami, Florida 33101(US)(72) Inventor: Parel, Jean-Marie
332, N.E. 92nd Street
Miami Shores, FL 33138(US)
Inventor: Yokokura, Takashi
6-15-18 Tamadaira
Hino, Tokyo 191(JP)
Inventor: Kobayashi, Katsuhiko
58-2 hataki
Ichihara, Chiba 299-01(JP)(74) Representative: Mongrédien, André et al
c/o SOCIETE DE PROTECTION DES
INVENTIONS 25, rue de Ponthieu
F-75008 Paris(FR)

(54) Noncontact laser microsurgical apparatus and method of using same.

(57) A noncontact laser microsurgical apparatus and method for marking a cornea of a patient's or donor's eye in transplanting surgery or keratoplasty, and in incising or excising the corneal tissue in keratotomy, and for tissue welding and for thermokeratoplasty. The noncontact laser microsurgical apparatus comprises a laser source and a projection optical system for converting laser beams emitted from the laser source into coaxially distributed beam spots on the cornea. The apparatus further includes a multiple-facet prismatic axicon lens system movably mounted for varying the distribution of the beam spots on the cornea. In a further embodiment of the method of the present invention, an adjustable mask pattern is inserted in the optical path of the laser source to selectively block certain portions of the laser beams to thereby impinge only selected areas of the cornea.

Fig. 1



EP 0 402 250 A2

BEST AVAILABLE COPY

NONCONTACT LASER MICROSURGICAL APPARATUS AND METHOD OF USING SAME

BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates to a microsurgical apparatus and, more particularly, a noncontact laser microsurgical apparatus adapted for use in cornea transplant surgery, keratoplasty, keratotomy, and other corneal surgery techniques.

Description of the Related Art

Despite advances in corneal preservation and transplantation techniques, postoperative astigmatism remains the most important complication limiting visual acuity after a corneal transplantation.

In order to reduce such postoperative astigmatism, U.S. Patent Application Serial Number 07/056,711 filed June 2, 1987 entitled "A Cornea Laser-Cutting Apparatus", assigned to the same assignee as the present application, discloses that trephination of either a donor cornea or a recipient cornea may be performed utilizing a laser cutting technique.

During penetrating keratoplasty, it is further necessary for a surgeon to align the circumferences of the donor corneal button and recipient cornea. To this end, there have been recently developed mechanical marking apparatus such as those described in Pflugfelder et al. "A Suction Trephine Block for Marking Donor Corneal buttons," Arch. Ophthalmol., Vol. 106, Feb. 1988, and Gilbard et al. "A New Donor Cornea Marker and Punch for Penetrating Keratoplasty," Ophthalmic Surgery, Vol. 18, No. 12, Dec. 1987.

However, such mechanical marking apparatuses directly contact and distort the cornea such that the marking process is not always precisely accomplished and sometimes results in post-keratoplasty astigmatism.

In radial keratotomy, mechanical contact type surgical utensils as shown in U.S. Patent Number 4,417,579 have been used to radially incise the cornea of a patient's eye. This surgical method is apt to cause strain and/or deformation of the cornea, and also results in postoperative astigmatism.

Noncontact microsurgery of the cornea would minimize distortion of the cornea tissue, as occurs in contact-type techniques, and would decrease the likelihood of producing postoperative astigmatism. The use of lasers provides the potential for such noncontact microsurgery.

Excimer lasers have been investigated in the past to produce linear corneal incisions or excisions. The argon fluoride excimer laser emitting at 193 nm has been shown to produce sharp, smooth-walled corneal cuts. More recently, the hydrogen fluoride, Q-switched Er:YAG, and Raman-shifted Nd:YAG lasers emitting at about 2.9 μ m (micro meters), which corresponds to the peak absorption wavelength of water, have been experimentally used to produce linear corneal incisions or excisions.

Industrial laser cutting by focusing the beam into a ring has been proposed as a method for drilling large diameter holes. The axicon, a diverging prismatic lens, has been used for such industrial purposes. An axicon system has been used by Beckman & Associates to study corneal trephination with a carbon dioxide laser. This experimentation is described in an article entitled "Limnectomies, Keratectomies and Kerastomies Performed With a Rapid-Pulsed Carbon Dioxide Laser," American Journal of Ophthalmology, Vol. 71, No. 6, (June 1971). In this article, Beckman et al. describe the use of an axicon lens in combination with a focusing lens to form an "optical trephine" and perform various corneal experiments with animal's. The diameter of the trephine was governed by the focal length of the focusing lens in these experiments. Therefore, to vary the diameter of the annular beam it was necessary to change the focusing lens which acted to change the width of the annular ring and, thus, varied the amount of tissue incised or excised by the laser. Moreover, changing the focusing lens requires a time consuming process for each patient or donor. In addition, the optical system proposed in the Beckman et al. article requires the use of multiple focusing lenses of different focal length.

Accordingly, it is an object of the present invention to provide a noncontact laser microsurgical apparatus and method of using the same which substantially eliminates strain and/or deformation on a cornea during and after trephination.

Yet another object of the present invention is to provide a noncontact laser microsurgical apparatus and surgical method which is capable of marking a recipient cornea and a donor corneal button with a suture track during keratoplasty, and which incises or excises selected portions of a cornea radially and/or paraxially during keratotomy.

Still another object of the present invention is to provide a noncontact laser microsurgical apparatus and surgical method which is capable of performing thermokeratoplasty for curing corneal refractive error and/or astigmatism of a patient's eye.

It is still another object of the present invention to provide a noncontact laser microsurgical apparatus and method capable of surgically "welding" donor tissue or synthetic material and recipient corneal tissue together thereby eliminating the necessity of suturing the donor and recipient parts to one another in penetrating and epikeratoplasty procedures.

It is still a further object of the present invention to provide a noncontact laser microsurgical apparatus and method wherein selected areas of the cornea may be caused to shrink so as to change the curvature of the natural lens thereby curing or alleviating corneal refractive error and/or astigmatism.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and attained by means of the instrumentalities and combinations particularly pointed out in the appended claims.

SUMMARY OF THE INVENTION

achieve the foregoing objects, and in accordance with the purposes of the invention as embodied and broadly described herein, the noncontact laser microsurgical apparatus of the present invention comprises means for generating laser beams; and means for projecting the laser beams onto a cornea. The projection means defines an optical axis and includes means for converging the laser beams. The projecting means further includes axicon optical means for forming the projected beams into a plurality of paraxially distributed spots on the cornea, and means for varying the radial position of the spots.

Preferably, the converging means includes a focusing lens and the axicon optical means includes at least one multiple-facet prismatic ("MFP") axicon lens mounted for movement along the optical axis of the projecting means.

The generating means may comprise an infrared pulse laser beam generator with a preferred wavelength of about 1.3 - 3.3 μm . Also, an ultraviolet laser source may be used such as an Argon fluoride laser emitting at 193 nm.

The projecting means preferably includes beam expander means for enlarging the radius of the laser beam emerging from the generating means.

The apparatus may also include aiming means for projecting visible laser beams onto the cornea substantially coincident with the positions at which

the laser beams projected through the axicon means impinge the cornea. The optical axis of the aiming means preferably overlaps with at least a portion of the optical axis of the projecting means. Preferably, the aiming means includes a visible laser beam source, and a mirror obliquely interposed between the beam expander means and the converging means for reflecting the visible laser beams and allowing the laser beams from the generating means to pass therethrough.

The apparatus of the present invention may also include mask means disposed in the optical axis for selectively blocking portions of the projected laser beams while transmitting the remaining portions of the projected laser beams therethrough. In this manner incisions or exisions in the corneal tissue may be made only in selected areas of the cornea corresponding to the transmitting portions of the mask means.

The present invention also provides a microsurgical method for ablating the cornea in selected areas by appropriate use of the disclosed apparatus. Moreover, by careful selection of the laser generating means the corneal tissue may be heated only sufficiently to cause shrinkage of the tissue in selected areas to alleviate astigmatism and/or corneal refractive error. Furthermore, by appropriate control of the selected laser generating means donor and recipient corneal tissue may be heated in abutting areas to cause the disparate tissue to adhere to one another in the manner of a surgical weld to thereby eliminate the need for sutures.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments and methods of the invention and, together with the general description given above and the detailed description of the preferred embodiments and method given below, serve to explain the principles of the invention. In the drawings:

Fig. 1 illustrates an optical system arrangement of a non-contact laser microsurgical apparatus incorporating the teachings of the present invention;

Fig. 2A is a plan view of a concave MFP axicon lens;

Fig. 2B is a cross-sectional view of the MFP axicon lens shown in Fig. 2A;

Fig. 3A is a plan view of a convex MFP axicon lens;

Fig. 3B is a side view of the MFP axicon lens shown in Fig. 3A;

Fig. 4 illustrates a donor cornea holding de-

vice which may be used with the apparatus and method of the present invention;

Fig. 5 is a plan view of a donor cornea marked by the apparatus of the present invention with spots defining a suture track;

Fig. 6 is a plan view of an alignment of a donor corneal button with a recipient cornea with spot marks defining a suture track in each;

Fig. 7 is a cross-sectional view of the alignment shown in Fig. 6;

Fig. 8 is a cross-sectional view of a cornea of a patient's eye marked with incisions formed during radial keratotomy;

Fig. 9 illustrates a plan view of the eye shown in Fig. 8;

Fig. 10 illustrates a plan view of a patient's eye which has been subjected to curved keratotomy;

Fig. 11 illustrates one embodiment of a mask means which may be used with the present invention;

Fig. 12 illustrates the angular orientation of the apertures defined by the masked means of Fig. 11;

Fig. 13 illustrates a cutaway side view of a portion of the cornea wherein portions of the stroma of the cornea have been treated by thermokeratoplasty;

Fig. 14 illustrates a front view of an eye which has been treated in selected areas utilizing the method and apparatus of the present invention with mask means;

Fig. 15 illustrates another embodiment of the mask means of the present invention;

Fig. 16 illustrates still another embodiment of the mask means of the present invention;

Fig. 17 is a cutaway side view of a portion of a cornea ablated by using the method and apparatus of the present invention and which illustrates the configuration of the cuts in the cornea which may be made utilizing the mask means of Figs. 15 and 16;

Fig. 18 illustrates still another embodiment of the mask means of the present invention;

Fig. 19 illustrates the fully open position of the mask means of Fig. 18;

Fig. 20 illustrates the fully closed position of the mask means of Fig. 18; and

Fig. 21 illustrates the relationship between the incised or excised depth of cuts made in the stroma and the circumferential position of annularly shaped laser beams projected by the mask means of Fig. 18.

Reference will now be made in detail to the presently preferred embodiments and method of the invention as illustrated in the accompanying drawings in which like reference characters designate like or corresponding parts throughout the several drawings.

An optical delivery system of a noncontact laser microsurgical apparatus incorporating the teachings of the present invention includes means for generating laser beams.

As illustrated in Fig. 1 and embodied herein, the generating means of apparatus 10 comprises a laser source 11 which generates pulsed laser beams that are capable of ablating the tissue of a living organ, i.e., a cornea. Lasers which meet the requirements described above may include HF (Hydrogen Fluoride) lasers, Er-YAG (Erbium-Yttrium Aluminum Garnet) lasers and Er/YSGG lasers (Erbium Yttrium Scandium Gallium Garnet) which emit infrared pulses having wavelengths of about 2.0 to about 3.0 μm , and preferably about 2.9 μm , and which have a pulse duration of less than 200 ns and an energy flux of greater than about 250 mj/cm^2 . Also operable with the present invention are ArF (Argon Fluoride) lasers which produce an ultra-violet laser beam having wavelengths of less than about 200nm with a pulse duration of about 10-23 ns and an energy flux of about 70 mj/cm^2 . Laser source 11 is connected to a radiation control switch 11a. When the control switch is moved to the "on" position laser source 11 generates infrared pulsed beams. Radiation control switch 11a is preferably capable of controlling the energy of the pulse beams by insertion of a neutral density filter (not shown) in a transmitting path thereof.

In instances where it is desirable to heat the corneal tissue without causing ablation, the laser source selected may be an C.W.HF, or Holmium, Nd:YLF or Nd:YAG laser emitting at a wavelength of 1.0 - 3.3 μm , a pulse duration of greater than 200 n sec, and an energy flux of about 250 mJ/cm^2 .

In accordance with the present invention, the apparatus includes means for projecting the laser beams along an optical axis onto the cornea. As embodied herein, the projecting means includes a beam expander means, generally referred to as 13, for expanding the laser beam generated by laser source 11. Beam expander means 13 includes a concave lens 14 and a convex lens 15. Laser beams emerging from convex lens 15 are formed in parallel and are in turn projected along optical axis O_1 . The beam expander means may also comprise a variable diverging beam expander comprised of a conventional zooming optical system or a pair of movable convex-concave axicon lenses described in the above-mentioned U.S. Patent Application Serial No. 056,711.

DESCRIPTION OF THE PREFERRED EMBODIMENTS AND METHOD

In accordance with the present invention, the apparatus includes means for converging the projected laser beams onto the cornea. As embodied herein, the converging means includes a condensing and focusing lens 17 which functions to condense and focus light passing therethrough onto a focal plane. The position of the focal plane FS is determined in accordance with the geometry of the lens as will be well understood by those skilled in the art. Beam expander 13 also acts to increase the laser beam diameter entering lens 17, thereby increasing the numerical aperture of the optical system. Consequently, the focal spot of the beam at the focal plane FS of lens 17 is reduced.

In accordance with a first embodiment of the present invention, the apparatus includes axicon optical means for forming the converged laser beams into a plurality of paraxially distributed beam spots on the cornea. As embodied herein the axicon optical means may comprise a multiple-facet prismatic ("MFP") lens 18.

As shown in Figs. 2A and 2B, axicon lens 18 may be configured with concave multiple-facet prisms (eight-facet prisms, for example) whose outer edges (prism bases) 100 are larger in width t than the optical axis portion 102 (length t') thereof. Axicon lens 18 may also be configured with convex multiple-facet prismatic lenses as shown in Figs. 3A and 3B whose outer edges (prism bases) 100 are larger in width t than optical axis portions 102 (length t') thereof. With reference to Fig. 6, the multiple-facet prism function of axicon lens 18 causes the converging laser beams emerging from lens 18 to be formed into a plurality of paraxially distributed beam spots 61 on cornea 31 of eye 30. The spots 61 are radially spaced from the apex P of cornea 31 and from optical axis O_1 . Preferably, the laser beam are converged onto cornea 31 of eye 30 (a patient's eye or donor's eye or tissue held in the holding device shown in Fig. 4) after reflection by a dichroic mirror 19 as shown in Fig. 1. As a result, cornea 31 is marked, excised, or incised by the laser beam energy at spots 61.

It is necessary to vary the cornea marking, excising, or incising diameters in keratoplasty and keratotomy. To this end, the present invention may include means for moving the axicon optical means along the optical axis O_1 . Furthermore, in order to carry out curved keratotomy in accordance with the present invention, means may be provided to rotate the axicon optical means about the optical axis. Furthermore, to perform radial keratotomy, means may be provided for moving the converging means along the optical axis.

As embodied herein, movement of the axicon optical means comprised of MFP lens 18, and movement of the converging means comprised of focusing lens 17 along optical axis O_1 , and rotation

of MFP axicon lens 10 about optical axis O_1 , may be carried out by a known electro-mechanical device (not shown) which may comprise a combination of stepping motors, for example, controlled by a microprocessor or minicomputer (not shown). By way of example and not limitation, model no. SPH-35AB-006 stepping motors manufactured by Tokyo Electronic Co., Ltd. may be used to move MFP lens 18 and focusing lens 17.

In accordance with the present invention, the microsurgical apparatus incorporating the teachings of the present invention may include aiming means for projecting visible light beams onto the cornea substantially coincident with the positions at which the laser beams are to impinge the cornea. As embodied herein, the aiming means comprises an aiming system 20 which includes a

He-Ne laser source 21 for generating visible light beams, beam expander means 22, and dichroic beam combiner 16. Beam expander means 22 may comprise a concave lens 23 and a convex lens 24. Dichroic beam combiner 16 is positioned in optical axis O_1 and is selected such that it functions to reflect incident He-Ne laser beams, while laser beams from source 11 pass therethrough. He-Ne laser beams from laser source 21 are enlarged in diameter by expander means 22, whose output laser beams, in turn, are projected onto condensing and focusing lens 17 after reflection by cold mirror 16. Thus, laser beams from source 21, which are reflected by mirror 16, are coincident with a portion of optical axis O_1 .

For observing the cornea and the He-Ne laser beams projected thereon, the noncontact laser microsurgical apparatus may also include viewing means comprised of an operation microscope 2, indicated by phantom lines in Fig. 1. The configuration and function of operation microscopes is well known in the ophthalmology field, therefore, its detailed description is omitted. By way of example and not limitation, a model no. OMS-600 microscope manufactured by TOPCON CORPORATION may be used.

An optical axis O_2 of operation microscope 2 is disposed to be coincident with a portion of optical axis O_1 of the noncontact laser microsurgical apparatus 10. In this configuration, mirror 19 functions as a half mirror for the laser beams from source 21, but as a complete mirror for the laser beams from source 11. An operator can determine an optimum diameter size of the laser beams projected onto the cornea by observing the laser beams from source 21 through operation microscope 2.

For marking a donor corneal button, the noncontact laser microsurgical apparatus may be coupled to a donor cornea holding device 40 as shown in Fig. 4. Donor cornea holding device 40 is provided with a housing cover 41 and a receiving

pedestal 42. Housing cover 41 includes an "O"-ring 43 disposed on an inner wall 44, and an annular magnet member 45. Receiving pedestal 42 includes a convex portion 46, a gas tube 47 extending from the center of the convex portion 46 to a pressure pump 49, a pressure gauge 40, and a magnet member 50 which is disposed opposite to and attracts the magnet member 45 of housing 41. In operation, a donor cornea or corneal scleral tissue 51 is mounted on the receiving pedestal 42 and the housing cover 41 is placed over button 51. Due to attractive forces between magnet members 45 and 50, "O"-ring 43 presses the corneal button tightly to the housing pedestal 42. Pressurized gas or fluid is supplied to the underside of the corneal tissue 51 through the tube 47 so that the donor tissue is maintained with a constant underside pressure which may be controlled to correspond to the intraocular pressure of the live eye, about 15mmHg - 20mmHg, by monitoring pressure gauge 48.

The steps of the method of the present invention for marking a cornea in transplanting surgery or keratoplasty can be carried out by using the noncontact laser microsurgical apparatus as hereinbelow described.

(1) A donor cornea or corneal scleral tissue 51 cut out from a donor eye is mounted on the cornea holding device 40. The donor cornea is pressurized at normal intraocular pressure (15 - 20mmHg) on the underside thereof by the fluid supplied from pump 49 through tube 47.

(2) The cornea holding device 40 is coupled to the laser microsurgical apparatus shown in Fig. 1 by appropriate mechanical means (not shown).

(3) Visible aiming laser light beams from source 21 are projected onto the cornea of a patient or onto a donor cornea through beam expander means 22, cold mirror 16, condensing lens 17, MFP axicon lens 18, and dichroic mirror 19.

(4) The visible aiming laser beams projected onto the cornea are observed through operation microscope 2. The diameter and position of the projected aiming laser beams are adjusted by moving the noncontact laser microsurgical apparatus and the operation microscope in tandem along optical axis O_2 .

(5) Next, axicon lens 18 is moved along optical axis O_1 so that the diameter or radial positions of paraxially distributed aiming laser beam spots from source 21 is adjusted to the desired size.

(6) After the diameter or radial positions of aiming laser beam spots has been set at an optimum size or radial position, control switch 11a is turned on and laser source 11 generates the infrared or ultraviolet pulsed laser beams.

(7) The pulsed laser beams are projected onto the cornea through the beam expander 13,

cold mirror 16, condensing lens 17, MFP axicon lens 18 and the dichroic mirror 19, respectively, to mark the donor cornea or corneal scleral tissue with spots 61 as shown in Figs. 5 and 6. When irradiating laser energy is properly controlled, light-point marking in accordance with this particular embodiment of the method of the present invention can be carried out on the epithellum of the donor cornea 51.

(8) The donor cornea may then be trimmed or cut about its periphery so as to match the diameter of a recipient hole in the recipient cornea and is then preserved. A noncontact laser microsurgical cutting apparatus as disclosed in U.S. Patent Application Serial Number 056,711, commonly assigned with this application and incorporated herein by reference, may be used to cut a donor corneal button and a recipient cornea.

(9) After the cornea holding device 40 has been removed from the noncontact laser microsurgical apparatus, a recipient eye is set up as shown in Fig. 1. The recipient cornea is also subject to marking and cutting as stated in the above steps (3) - (8), provided, however, that the diameter and radial positions of the paraxially distributed beam spots 61 on the recipient cornea is made slightly larger than the diameter and radial positions of the beam spots 61 on the donor corneal button.

(10) Next, the donor corneal button 51 is aligned with the recipient cornea 52 by matching the paraxially distributed spots 61 as shown in Fig. 6. The cornea has epithelium 71, stroma 72, and endothelium 73 as shown in Fig. 7. The paraxially distributed spots 61 on the donor corneal button 51 and recipient cornea 31 may be marked only on the epithelium 71, or through the epithelium, the Bowman's layer and to a predetermined depth (for example 100 μ m) into the stroma, to create suture tracks.

(11) Suturing is then carried out through the paraxially distributed dots as indicated by dotted line 74 in Fig. 7.

By carrying out the steps of the first embodiment of the method of the present invention as described above, eight dots are marked on each of the donor corneal button 51 and the recipient cornea 31 as shown in Fig. 6.

When sixteen spots are required to be marked, after the first marking steps are carried out as described above axicon lens 18 may be rotated by a predetermined angle about optical axis O_1 , for example 22.5°, to mark an additional 8 spots (denoted by "X"). Similarly, an additional eight suture tracks are marked on the recipient cornea 31 so that sixteen symmetrical spots are marked on both the donor corneal button and the recipient cornea.

The noncontact laser microsurgical apparatus

of the present invention may also be utilized in keratotomy, as will be described hereinbelow.

The diameter or radial positions of the distributed beam spots can be adjusted by moving MFP axicon lens 18 along optical axis O_1 as already explained hereinabove in connection with keratoplasty. Moreover, in radial keratotomy where the radial incisions or excisions made in the cornea extend outwardly from the apex P of the cornea, the focal plane FS of the laser beams must be varied since the curvature of the cornea causes the radial incision or excisions in the cornea to be formed at varying distances from the laser source as the incision or excision moves progressively outward from the apex P of the eye. Thus, to insure that the laser beams are brought to focus in the correct focal plane corresponding to the varying depths or distances at different radial positions on the cornea, the focal plane FS of the apparatus of the present invention is adjusted by moving condensing lens 17 along optical axis O_1 (shown by arrow B in Fig. 1).

In radial keratotomy, wherein incisions or excisions are produced in the stroma and are oriented radially from the center of the cornea to the outer edge of the cornea, the curvature of a cornea is measured in advance by a keratometer so as to predict the distance of the focal plane of the laser beams at all radial positions on the cornea. With reference to Fig. 8, after the initial focal points "C" have been set in the upper portion of stroma 72, MFP axicon lens 18 is moved axially and preferably continuously within a predetermined range along optical axis O_1 so that radial incisions or excisions 81, 81', 82 and 82' in stroma 72 may be made along the curvature of the cornea from points "C" toward points "D" as shown in Figs. 8 and 9, Fig. 8 being a cutaway side view of Fig. 9 along lines 8-8. Simultaneously, condensing lens 17 is moved axially and preferably continuously along optical axis O_1 to adjust the focal plane of the laser beams to correspond to the radial position of the cornea at which the incision or excision is being made.

Laser energy from source 11 may be set to a sufficient energy to ablate and incise or excise the tissue of stroma 72 to a desired depth Δ .

In curved keratotomy, wherein the excisions or incisions in stroma 72 are oriented as curved portions, i.e., as circumferential arcs 93 spaced predetermined and substantially constant radial distance from the apex or center of the cornea, MFP axicon lens 18 may be comprised of at least one two-facet prismatic lens. After focal points "C" have been set in stroma 72, MFP axicon lens 18 is rotated about optical axis O_1 within a predetermined rotating angle while laser source 11 is emitting beams of sufficient energy to ablate the

stroma, thereby producing incisions or excisions in the stroma as illustrated in Fig. 10.

In another embodiment of curved keratotomy utilizing the apparatus and method of the present invention, MFP axicon lens 18 may be composed of at least one MFP lens having more than two facets, eight facets for example, which is rotatable about the optical axis O_1 . Furthermore, apparatus 10 may include mask means, disposed between focusing and condensing lens 17 and cold mirror 16, for selectively defining at least one open aperture in optical axis O_1 . In the present preferred embodiment, the mask means includes mask 25 having three mask units 26, 27, and 28 as shown in Fig. 11. Mask units 26 and 27 each include a pair of transparent portions 26a, 27a configured as 120° fan-shaped aperture angles 110 for transmitting laser beams emerging from cold mirror 16 therethrough, and a pair of opaque portions 26b, 27b configured as 60° fan-shaped aperture angles 112 for blocking the laser beams emerging from cold mirror 16.

In accordance with the present invention, means may be provided for rotating mask units 26 and 27 in opposite directions, designated by arrows "a" and "b" in Fig. 11, relative one another about optical axis O_1 to change aperture angles 110 and 112 within a prescribed range, for example, between 60° - 120° . As embodied herein the rotating means may comprise a stepping motor (not shown) controlled by a microprocessor (not shown). One skilled in the art will readily identify such motors and controllers, and, since the configuration of these motors and controllers do not themselves constitute any portion of the present invention, a detailed description is omitted. However, by way of example, a model no. SPH-35AB-006 type motor manufactured by Tokyo Electric Co., Ltd. may be used. Also, any suitable controller such as an IBM PC/AT may be used to control the motor.

The mask means may also include a mask unit 28 having a pair of semicircular portions 28a, 28b. Semicircular portion 28a is transparent to transmit laser beams therethrough, and semicircular portion 28b is opaque to the laser beams. Means may be provided to insert and remove mask unit 28 within optical axis O_1 to selectively block a portion of the laser beams from source 11, the blocked portion corresponding to the position of opaque semicircular portion 28b. The mask units 26, 27 and 28 are constructed to be able to rotate in unison about optical axis O_1 to selectively position the apertures defined by masks 25 and 26 in optical axis O_1 .

In this embodiment, after aperture angles 110 and 112 have been selected by individual opposite rotation of masks 25 and 26, and after the inclination angle β illustrated in Fig. 12 has been selected

by common rotation about axis O_1 of masks 25 and 26 as a unit, the MFP axicon lens 18 rotates continuously in predetermined minute steps about optical axis O_1 for incising or excising the cornea.

The noncontact laser microsurgical apparatus and method of the present invention has further applications to thermokeratoplasty as will be described hereinbelow.

In thermokeratoplasty, for curing corneal refractive errors, e.g., hyperopia, myopia and/or astigmatism, laser source 11 may comprise an infra-red pulse type laser that emits a laser pulse having wavelengths of about 1.3 μm to about 3.3 μm . Laser source 11, in this embodiment, may comprise a Ho (Holmium) laser, for example, emitting at a wavelength of about 2.1 μm .

With reference to Fig. 13, in thermokeratoplasty for curing hyperopia, for example, after the focal points "C" have been set at points "e" with an optimum diameter and an optimum depth " Δ " in the stroma 72 by independently moving focusing and condensing lens 17 and MFP axicon lens 18 along optical axis O_1 as has been described above, the Ho laser source 11 generates and projects the pulse laser beams onto the points "e".

Eight burns are formed instantly and simultaneously at the points "e" and cause shrinkage of the tissue of the stroma in the vicinity "f" around the points "e." The thermal effect of the laser causing shrinkage of the tissue about points "e" leads to a change of the shape of the cornea to alleviate hyperopia. Here, Do shows a diameter of cornea button.

With reference to Fig. 14, in thermokeratoplasty for alleviating astigmatism, mask unit 25 may be used to selectively define the angular position β and the angle α , and to set the number of spots 61 projected onto the points "e". The thermal effects of the laser and the resulting shrinkage of tissue in vicinity "f" lead to a change of the shape of the cornea to alleviate the astigmatism. Here S denotes a beam spot coming into a cornea.

In the embodiments of the method and apparatus of the present invention described above, the tissue of the cornea is impinged with laser beams of sufficient energy and for a sufficiently long time that the cornea is ablated by causing the fluids comprising the corneal tissue to go from solid or liquid phases to a gaseous phase. Such ablation is termed photo-vaporization when carried out using a hydrogen-fluoride short pulsed, and photodecomposition when carried out using an argon-fluoride excimer laser.

In other embodiments of the surgical method of the present invention, it is desirable not to vaporize or decompose the corneal tissue. Since the corneal tissue is comprised almost entirely of water, this means that under atmospheric pressure the tem-

perature to which the corneal tissue is raised must be less than 100°C. This is best carried out with lasers having longer pulse durations, such as a long-pulsed C.W.HF laser, Nd:YAG, Nd:YLG laser, or a Holmium laser each having pulse durations greater than 200 ns and an energy flux of about 250 mJ/cm².

The inventors herein have discovered that above 60°C, the corneal tissue becomes adhesive and will begin to shrink. Thus, in one embodiment of the method of the present invention, selected areas of the cornea are impinged with laser beams having sufficient energy and for a sufficient time to heat the corneal tissue to less than about 100°C to thereby cause shrinkage of the corneal tissue in those selected areas. In this manner the shape of the cornea and the curvature of the crystalline lens of the eye can be modified to alleviate astigmatism and/or corneal refractive error. Moreover, any of the embodiments of the apparatus of the present invention may be used in the practice of this method for shrinking corneal tissue to thereby control and define the selected areas of the cornea in which shrinkage is desirable.

In a further embodiment of the method of the present invention, where, during corneal transplant surgery, the donor cornea button has been placed in the recipient cornea, the abutting edges 51' of the donor button and recipient cornea may be impinged with laser beams of sufficient energy and duration to heat the abutting edges 51' to between about 60°C - 85°C. For this embodiment it is desirable to use a laser source having a pulse duration of greater than about 200 ns, a frequency of about 2.0-3.0 μm , and an energy flux less than about 250 mJ/cm². In this manner, the tissue at the edges of the button and recipient hole 31' become adhesive and attach to one another in a type of surgical weld thereby eliminating the need for sutures. This "welding" method may also be employed in epi-keratoplasty to attach a piece of cornea-like tissue over a whole recipient cornea to act in the manner of a contact lens. This "cornea-like tissue" may be human, animal or synthetic. This "welding" can be performed all the round by using a conical axicon lens 18'.

In a second embodiment of the present invention, a conical axicon lens 18' illustrated with the dot-dash line in Fig. 1 may be used in place of MFP axicon lens 10. In such an embodiment the conical axicon lens need not be rotated about optical axis O_1 to perform curved keratotomy because the conical axicon lens converts the laser beams exiting from condensing and focusing lens 17 into annular beams and projects them toward the patient's cornea.

Each of Figs. 15 and 16 illustrate alternative embodiments of the mask means. In both alter-

native embodiments of the mask means, two masks are spaced from one another on optical axis O_1 . Each mask is identical in configuration. Therefore, only one of the masks, mask 130, is illustrated in Figs. 15 and 16.

By way of example and not limitation, mask 130 may comprise a metal plate having two fan-shaped opaque portions 132 and 134, and side edges 136 and 138 which are formed in a concave arc as shown in Fig. 15, or in a convex arc as shown in Fig. 16. Since the energy density of arc laser beams emerging through the aperture defined by side edges 136 and 138 decreases gradually along the radial direction of the arcs defined by the side edges 136 and 138, the depth of the incised or excised cut on the patient's cornea 31 shallowed gradually and smoothly at both end portions 93 and 93' as shown in Fig. 17 such that delicate or subtle curved keratotomy may be carried out utilizing the method and apparatus of the present invention.

Fig. 18 illustrates a still further embodiment of the mask means. Therein, masks 150 and 152 having wedge shaped portions 154 and 156, respectively, may be moved simultaneously or individually in opposite directions relative one another along arrows 158 and 160, respectively. In this manner, the aperture angle α defined by the edges of the wedge portions 154 and 156 may be selected in a predetermined manner. Furthermore, masks 150 and 152 may be rotated individually or in unison by any suitable motor or manual means about optical axis O_1 to selectively define the position angle β of the incised or excised cuts on the cornea of the eye.

Utilizing the mask means illustrated in Fig. 18, masks 150 and 152 may be moved towards each other along directions 150 and 160, respectively, during impingement of the cornea with laser beams. In Fig. 19, masks 150 and 152 are in the fully open state such that no portion of the cornea is blocked by wedge portions 154 and 156. As masks 150 and 152 are moved closer together as illustrated in Fig. 18, wedge portions 154 and 156 selectively block larger portions of the cornea from the laser beams emitted by source 11. In Fig. 20, wedge portions 154 and 156 overlap each other to fully block the cornea from any laser beams emitted by source 11.

Utilizing the mask means illustrated in Fig. 18 in combination with a conical MFP axicon lens, the annular laser beams P projected onto the cornea are changed in total emitted energy in accordance with the circumferential positions d as illustrated in Fig. 19. Therefore, the incised or excised depth D of the cuts made in the stroma are gradually changed in depth to resemble a sine curve as illustrated in Fig. 21. In this manner, alleviation of

corneal astigmatism may be carried out more delicately and subtly utilizing the teachings of the present invention to cure not only corneal astigmatism, but also corneal spherical power error.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details, representative devices, and illustrative examples shown and described. Accordingly, departures may be made from such details without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

Claims

1. A noncontact laser microsurgical apparatus, comprising:
 - means for generating laser beams;
 - means for projecting said laser beams toward a cornea, said projecting means defining an optical axis, and including:
 - means for converging the laser beams onto the cornea; and
 - axicon optical means for forming the converged laser beams into a plurality of paraxially distributed beam spots on the cornea.
2. A noncontact laser microsurgical apparatus as in claim 1, wherein said converging means includes condensing lens means for focusing said laser beams on the cornea.
3. A noncontact laser microsurgical apparatus as in claim 1, wherein said axicon optical means includes at least one multiple facet prismatic lens.
4. A noncontact laser microsurgical apparatus as in claim 1, wherein said projecting means include beam expander means for enlarging the radius of said laser beams, and said converging means includes condensing lens means for focusing said laser beams on the cornea.
5. A noncontact laser microsurgical apparatus as in claim 1, wherein said projecting means include beam expander means for enlarging the radius of said laser beams.
6. A noncontact laser microsurgical apparatus as in claim 5, wherein said beam expander means includes a variable diverging beam expander.
7. A noncontact laser microsurgical apparatus as in claim 1, wherein said generating means includes an infrared pulsed laser beam generator.
8. A noncontact laser microsurgical apparatus as in claim 7, wherein said pulsed laser beam generator comprises an HF an Er-YAG laser, Er:YSGG, or Holmium/YAG beam source.
9. A noncontact laser microsurgical apparatus as in claim 1, wherein said pulsed laser beam generator comprises an ultra-violet laser beam

source.

10. A noncontact laser microsurgical apparatus as in claim 7, wherein the wavelength of beams generated by said infrared pulsed laser beam generator is within about 1.3 μm to about 3.3 μm .

11. A noncontact laser microsurgical apparatus as in claim 1, further including aiming means for projecting visible light beams onto the cornea at positions substantially coincident with positions to be impinged by said laser beams.

12. A noncontact laser microsurgical apparatus as in claim 11, wherein the optical axis of said aiming means overlaps a portion of the optical axis of said projecting means.

13. A noncontact laser microsurgical apparatus as in claim 11, wherein said aiming means includes a visible laser beam source, and mirror means, obliquely interposed between said generating means and said converging means, for reflecting the visible laser beams emitted by said aiming means and for transmitting the laser beams from said generating means therethrough.

14. A noncontact laser microsurgical apparatus as in claim 1, including means for adjusting the radial position of said beam spots relative to the apex of the cornea.

15. A noncontact laser microsurgical apparatus as in claim 1, including means for rotating said oxicon optical means relative to said optical axis of said projecting means.

16. A noncontact laser microsurgical apparatus as in claim 1, including means for moving said converging means along said optical axis.

17. A noncontact laser microsurgical apparatus as in claim 1, further including mask means for selectively defining at least one light transmissive aperture and at least one opaque aperture in said optical axis of said projecting means.

18. A noncontact laser microsurgical apparatus as in claim 17, wherein said mask means includes first and second masks spaced from one another and aligned on said optical axis, each said mask including at least two fan-shaped light transmissive portions which define selected open angles therebetween when viewed along said optical axis, and means for rotating said first and second masks in opposite directions relative one another to selectively adjust said predetermined angles formed between said transparent portions of said masks.

19. A noncontact laser microsurgical apparatus as in claim 17, wherein said mask means includes at least two mask plates each having a wedge portion, and means for moving said wedge portions into and out of said optical axis of said projecting means to selectively block portions of said laser beams emitted by said generating means.

20. The noncontact laser microsurgical apparatus of claim 17, wherein said mask means includes

at least two mask plates each having a wedge portion selectively movable into and out of said optical axis of said projecting means, and means for rotating at least one of said masks about said optical axis.

21. A noncontact laser microsurgical apparatus, comprising:

means for generating laser beams;

means for projecting said laser beams toward a cornea, said projecting means defining an optical axis, and including:

means for converging the laser beams onto the cornea;

conical axicon optical means for forming the converged laser beams into annularly shaped beams; and

mask means for selectively blocking a portion of said laser beams and for transmitting the remaining portion of said laser beams to thereby impinge the cornea with said laser beams at selected positions corresponding to said portion of said mask means through which said laser beams are transmitted along said optical axis.

22. A noncontact laser microsurgical apparatus as in claim 21, wherein said mask means forms at least one aperture for passing the laser beams therethrough, and includes means for changing the area of said aperture.

23. A noncontact laser microsurgical apparatus as in claim 22, wherein said mask means includes first and second masks each including two fan-shaped transparent portions and two fan-shaped opaque portions, said transparent portions defining predetermined open angles between the respective edges thereof which correspond to said at least one aperture of said mask means, and said means for changing the area of said at least one aperture includes means for rotatably mounting said masks in said optical axis such that said masks may be rotated independently of one another to vary said open angles defined by said transparent portions.

24. The apparatus of claim 23, including means for rotating said masks in unison to selectively adjust the angular position of said apertures about said optical axis.

25. A noncontact laser microsurgical apparatus as in claim 23, wherein said mask means further includes a third mask having semicircularly-shaped transparent and opaque portions for defining additional patterns of said mask means.

26. A noncontact laser microsurgical apparatus as in claim 25, including means for rotatably mounting said third mask in said optical axis.

27. A noncontact laser microsurgical apparatus as in claim 22, wherein said mask means includes at least two mask plates each having a wedge-shaped end portion, and means for moving said wedge-shaped portions of said mask plates into

and out of said optical axis.

28. The apparatus of claim 27, including means for rotating at least one of said wedge-shaped portions about said optical axis.

29. A non-contact microsurgical method for marking a cornea with suture tracks, comprising the steps of:

a) generating laser beams of sufficient energy to ablate the tissue of the cornea;

b) projecting the laser beams along an optical axis toward the cornea;

c) converging the projected laser beams onto the cornea;

d) forming the converging laser beams into a plurality of paraxially distributed beam spots on the cornea, said beam spots defining the suture tracks.

30. The method of claim 29, wherein the step of forming the converging laser beams into a plurality of paraxially distributed beam spots includes the substep of passing said converging laser beams through a multiple facet prismatic lens disposed in said optical axis.

31. The method of claim 30, including the further step of varying the radial position of the beam spots relative to the apex of the cornea.

32. The method of claim 31, wherein the step of varying the radial position of the beam spots includes the substep of selectively moving the multiple facet prismatic axicon lens along the optical axis.

33. The method of claim 29, wherein the cornea being marked comprises a donor corneal button which has been surgically removed from a donor cornea.

34. The method of claim 29, wherein the cornea being marked comprises a recipient cornea which has had the central portion thereof surgically removed to receive a donor corneal button.

35. The method of claim 29, wherein steps (a)-(d) are performed to mark a donor corneal button with a predetermined number of suture tracks, and steps (a)-(d) are repeated to mark a recipient cornea, having the central portion thereof removed, with at least the same predetermined number of suture tracks, the suture tracks marked on said recipient cornea being radially spaced from and aligned with the suture tracks marked on said donor corneal button.

36. The method of claim 35, including the further step of:
suturing the donor corneal button into the recipient cornea by passing surgical thread through respective aligned pairs of suture tracks in the donor corneal button and recipient cornea.

37. A non-contact microsurgical method for ablating a cornea at selected positions, comprising the steps of:

generating laser beams having sufficient energy to

ablate the cornea;

projecting said laser beams along an optical axis toward the cornea;

converging said projected laser beams onto the cornea;

forming the converged laser beams into annularly shaped beams;

selectively blocking a portion of said laser beams and transmitting the remaining portion of said laser beams along said optical axis to thereby ablate the cornea at selected positions corresponding to the configuration of the portions of said laser beams transmitted along said optical axis.

38. The method of claim 37, wherein the step of selectively blocking and transmitting portions of said laser beams includes the substep of inserting a mask means in said optical axis, the mask means having opaque portions corresponding to said blocked portion of said laser beams and transparent portions corresponding to said transmitted portions of said laser beams.

39. The method of claim 37, including the step of adjusting the relative sizes of the blocked portion and the transmitted portion of said laser beams.

40. The method of claim 38, wherein the mask means comprises at least first and second masks each including opaque portions and transparent portions, and including the further step of adjusting the relative sizes of the blocked and the transmitted portions of the laser beams by rotating the first and second masks relative to one another to thereby vary the relative sizes of the opaque and transparent portions of the masks.

41. The method of claim 38, including the further step of adjusting the angular positions of the blocked portions and transmitted portions of the laser beams relative to the optical axis by rotating the mask means.

42. A non-contact microsurgical method for alleviating astigmatism and/or corneal refractive error of an eye, comprising the steps of:
generating laser beams having a predetermined energy flux;

projecting the laser beams along an optical axis toward the cornea;

converging the projected laser beams onto the cornea;

impinging the cornea with the laser beams at selected areas for a sufficient time to heat the impinged areas to less than about 100°C to thereby shrink the corneal tissue in the selected areas without causing ablation in said selected areas.

43. The method of claim 42, wherein the laser beams are generated with a laser having a wavelength of about 1.3 - 3.3 μm , a pulse duration greater than about 200 ns, and an energy flux of about 250 mJ/cm^2 .

44. A non-contact microsurgical method for

surgically attaching a donor corneal button into a recipient cornea, comprising the steps of:

placing the donor corneal button in the recipient cornea;

generating laser beams having a predetermined energy flux; 5

projecting the laser beams along an optical axis toward the cornea;

converging the projected laser beams onto the cornea; 10

impinging the abutting edges of the donor corneal button and the recipient cornea with the converged laser beams for a sufficient time to raise the temperature of the corneal tissue of the abutting edges to between about 60° C - 85° C thereby causing the tissue of the donor button and recipient cornea to adhere to one another. 15

45. The method of claim 44, wherein the laser beams are generated with a laser having a pulse duration of greater than about 200 ns, a frequency of about 1.3 - 3.3 μ m, and an energy flux of about 250 mJ/cm². 20

46. A non-contact microsurgical method for surgically attaching a layer of cornea-like tissue onto a recipient cornea, comprising the steps of: placing the layer of the cornea-like tissue onto the recipient cornea; 25

generating laser beams having a predetermined energy flux;

projecting the laser beams along an optical axis toward the recipient cornea and cornea-like tissue layer; 30

converging the projected laser beams onto the cornea-like tissue layer; and

impinging the cornea-like tissue layer in selected areas with the converged laser beams for a sufficient time to raise the temperature of the selected areas of the cornea-like tissue layer and the areas of the recipient cornea tissue immediately below the selected areas of the cornea-like tissue layer to between about 60° C - 85° C thereby causing the cornea-like tissue layer to adhere to the recipient cornea in the selected areas. 35 40

47. The method of claim 46, wherein the laser beams are generated with a laser having a pulse duration of greater than about 200 ns, a frequency of about 1.3 - 3.3 μ m, and an energy flux of about 250 mJ/cm². 45

50

55

Fig. 1




Fig.2A




Fig.2B




Fig.3A




Fig.3B




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig.14




Fig.15




Fig.16




Fig. 17




Fig. 18




Fig. 19




Fig. 20





Fig. 21



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets




(11) Publication number:

0 402 250 A3

(12)

EUROPEAN PATENT APPLICATION(21) Application number: **90401539.3**(51) Int. Cl.⁵: **A61B 17/36, A61F 9/00**(22) Date of filing: **06.06.90**(30) Priority: **07.06.89 US 363174**(43) Date of publication of application:
12.12.90 Bulletin 90/50(84) Designated Contracting States:
DE ES FR GB IT(88) Date of deferred publication of the search report:
27.12.91 Bulletin 91/52(71) Applicant: **UNIVERSITY OF MIAMI**
School of Medicine, Department of
Ophthalmology, 1638 N.W. 10th Avenue
Miami, Florida 33101(US)(72) Inventor: **Parel, Jean-Marie**
332, N.E. 92nd Street
Miami Shores, FL 33138(US)
Inventor: **Yokokura, Takashi**
6-15-18 Tamadaira
Hino, Tokyo 191(JP)
Inventor: **Kobayashi, Katsuhiko**
58-2 hataki
Ichihara, Chiba 299-01(JP)(74) Representative: **Mongrédien, André et al**
c/o SOCIETE DE PROTECTION DES
INVENTIONS 25, rue de Ponthieu
F-75008 Paris(FR)(54) **Noncontact laser microsurgical apparatus and method of using same.**

(57) A noncontact laser microsurgical apparatus and method for marking a cornea of a patient's or donor's eye in transplanting surgery or keratoplasty, and in incising or excising the corneal tissue in keratotomy, and for tissue welding and for thermokeratoplasty. The noncontact laser microsurgical apparatus (10) comprises a laser source (11) and a projection optical system for converting laser beams emitted from the laser source into coaxially distributed beam spots (61) on the cornea (31). The apparatus further includes a multiple-facet prismatic axicon lens system (18) movably mounted for varying the distribution of the beam spots (61) on the cornea. In a further embodiment of the method of the present invention, an adjustable mask pattern (25-28) is inserted in the optical path of the laser source to selectively block certain portions of the laser beams to thereby impinge only selected areas of the cornea.

Fig. 1**EP 0 402 250 A3**



European Patent
Office

PARTIAL EUROPEAN SEARCH REPORT
which under Rule 45 of the European Patent Convention
shall be considered, for the purposes of subsequent
proceedings, as the European search report

Application number
EP 90401539

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. Cl. 5)
X	WO-A-8707829 (G. RODENSTOCK INSTRUMENTE GMBH) * claims 1-3,5; page 8, lines 4-20; figures 1-3 *	1-5,7,8	A61B17/36 A61F9/00
A		9,10,17,21	
X	FR-A-2594686 (COMPAGNIE INDUSTRIELLE DES LASERS CILAS ALCATEL) * claims 1-3,9; figure 4 *	1,9,11,14,15	
A		13	
Y	US-A-4648400 (SCHNEIDER et al.) * claims 1-5,11,27; column 8, lines 1-15; figure 6 *	9,10,17,21	
A		18,23,28	
A	US-A-4549787 (TANNER) * claim 3; figures 2-4 *	21	
A	WO-A-8700748 (ARON-ROSA) * claims 1,9,10 *	1	TECHNICAL FIELDS SEARCHED (Int. Cl. 5)
A	EP-A-0191688 (BIOPHYSIC MEDICAL S.A.) * claims 1,2,5,16-18	1,16	A61B A61F
INCOMPLETE SEARCH <p>The Search Division considers that the present European patent application does not comply with the provisions of the European Patent Convention to such an extent that it is not possible to carry out a meaningful search into the state of the art on the basis of some of the claims.</p> <p>Claims searched completely: 1-28 Claims searched incompletely: Claims not searched: 29-47 Reason for the limitation of the search: methods for treatment of the human or animal body by surgery (art. 52(4) EPC)</p>			
Place of search BERLIN		Date of completion of the search 15.09.1991	Examiner PAPA, E.
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO Form 1305.1 03/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.